

# CARMIX 2.5TT



**MIXING UNIT:** Drum capacity 3.450 liters. Concrete drum output: 2,5 m<sup>3</sup>. EN 206-1 IN SLUMP S1 Class, yield not vibrated. Double mixing screws, cover for emergency unloading. Drum rotation by hydraulic motor and planetary reducers. Mixing and discharging speed independent from r.p.m. of diesel engine. Discharging by reversing drum. The mixing unit is slewing hydraulically through 270° for high discharge at 1,9 m on the four sides of the vehicle.



**ENGINE:** Perkins 1104D-44T Turbo-Diesel Tier 3, water-cooled, 4 cylinders. Rated power KW 62,5 (84 HP) set at 2.200 rpm. Engine mounted transversal on the rear.



**TRANSMISSION:** Hydrostatic Bosch Rexroth. Pump and motor are connected to the differentials through a 2 speed reducer (working and transfer). 4 wheel drive and steering.



**AXLES:** Dana Spicer with oil bath disc brakes and planetary reducers.



**SPEED:** Working speed from 0 to 9 km/h, road transfer from 0 to 25 km/h. Electric servo control.



**CABIN:** Front cab on side of loading shovel. ROPS-FOPS (UNI 11023) type complete with double closing door. Clima, air conditioning heater available upon request.



**HYDRAULIC SYSTEM:** Three circuits. 2 variable outlet pumps for hydrostatic transmission and drum rotation. 2 gear pumps for services. Inlet and outlet filter. Heat exchanger water/oil-air type.



**JOYMIX:** All hydraulic functions of shovel controlled by a single - fully servo controlled Joystick.



**WEIGHING:** Electronic system. "Load cells" acting on the drum, display and printer in the cab. (on request)



**LOADING SHOVEL SELF ARTICULATED:** Effective capacity per load 400 liters, complete with hydraulic opening gate.



**CHUTE:** Slewing and hydraulically tilting. Fitted with two pins easily detachable to increase the discharge height. 2 extra chutes included.



**WATER SYSTEM:** Self-contained. Hydraulic driven water pump 400 lt/min, water meter, washing outlet. High pressure water pump (on request).



**GRADIENT:** Fully loaded 30%.



**BRAKES:** Oil bath disc brakes inside differential axles. Twin independent circuits. Negative hydraulic parking brake.



**TYRES:** Off road industrial type 12.5-20 PR 12.



**STEERING:** Hydrostatic. 3 ways steering. Radius: internal: mm. 1500, external mm 3500.



**ELECTRIC SYSTEM:** 12 Volt. 120 Ah battery for electric starter and road lighting. Safety battery cut-off.



**TANKS:** Water: 2x270 liters. Diesel: 105 liters. Hydraulic oil: 80 liters.



**CHASSIS:** Steel profile specially engineered for off-road operations.



**WEIGHT:** About Kg. 6.000. Equally distributed on both axles.



**SAFETY:** Machine equipped with checking and block valves for maximum safety of the operator. Self control avoids drum to slew if shovel's arm is lifted.



**CATALOGUE:** The machine is equipped with Use and Maintenance and Spare Parts Manuals according to CE regulations.



## ACCESSORIES ON DEMAND

### EUROPEAN VERSION: PERKINS 904J-E36TA TURBO-DIESEL STAGE V 55.4 KW (74HP)

Electronic weighing system "LOAD CELLS" with printer

High-pressure washing pump (90 BAR) with gun

Clima (air conditioning plus heater)

Spare wheel

Additional discharging chute (cm 100)

